



Critical Environment Technologies

Unit 145, 7391 Vantage Way Delta, BC, Canada V4G 1M3

phone 604-940-8741 fax 604-940-8745

www.critical-environment.com

DST-S SERIES SPECIFICATION SHEET

DIGITAL TRANSMITTERS WITH SOLID STATE REFRIGERANT SENSORS

Dimensions:	<u>Standard Enclosure</u>	<u>Optional Watertight Enclosure</u>
	Size: 4.5" x 6.1" x 2.6" (115mm x 155mm x 66mm)	Size: 5" X 5" X 3" (125mm x 125mm x 75mm)
	Weight: 9 ounce (255 g)	Weight: 12 ounces (340 g)
	* Optional duct sampling kits available for duct monitoring	
Construction:	Rugged PVC (with hinged door)	Rugged Polycarbonate (with hinged door)
Sensors:	Type: Temperature compensated, non-specific , solid-state	
	Life span: approximately 5 years	
	Calibration: one to two times per year (application dependent)	
Sensor Range:	0 – 2000 ppm standard, calibrated to the desired refrigerant gas	
System Power:	24 VDC nominal (approximately 80 to 120 mA current draw)	
Temperature:	-20 C. to +40 C. (-4 F. to +104 F)	
Humidity:	0 to 90% non-condensing (some drifting will occur from increased humidity)	
Indicators:	LED power, fault, alarm indicator	
Signal:	Digital output on RS 485 communication bus, linearized	
Accuracy:	+/- 10% of measured signal (above 35 ppm)	
Cross sensitivity:	Many other gases and especially vehicle exhaust	
Fusing:	Automatic resetting thermal overload fuse (reset capabilities to 500 times)	
Wiring:	2 wires low voltage power, 2 wires communication bus	
Sensor Mounting:	Heavier than air, 6" from floor	
Notes:	1) Never install gas detection sensors in the direct path of moving air, such as exhaust fans, make-up air fans, elevator shafts, ramps, ducts, etc. 2) If vandalism is a concern, heavy metal (16 gauge) transmitter guards are available. They are easily installed over the transmitters.	